



 **PUMPS**

QJ/QS 系列潜水泵 QJ/QS SERIES SUBMERSIBLE PUMP



郑州市神龙泵业有限公司
地址：河南省郑州市高新区电子商务产业园
邮箱：Info@apkump.com
Info@dragonpump.com
电话：**0086-371-56066186**
网址：www.dragonpump.com
微信/Whatsapp：**008613783669139**
脸书/优象：apkumps@gmail.com
领英/推特：info@apkump.com

ZHENGZHOU SHENLONG PUMP INDUSTRY CO., LTD
Add: E-commerce Industrial Park, High-tech Zone,
Zhengzhou City, Henan Province, China
Email: info@apkump.com
info@dragonpump.com
Tel: **0086-371-56066186**
Web: www.dragonpump.com
Whatsapp/Wechat: **008613783669139**
Facebook/YouTUBE: apkumps@gmail.com
LinkedIn/Twitter: info@apkump.com

郑州市神龙泵业有限公司
ZHENGZHOU SHENLONG PUMP INDUSTRY CO.,LTD

基本参数表 Basic Parameter Table

型号 Model	电机功率 Motor Power		流量范围 Flow Range	扬程范围 Head Range	电缆 Cable	出口尺寸 Outlet Size	额定电流 Rated Current	功率因数 Power Factor
	kW	hp	m ³ /h	m	mm ²	Inch (")	A	cosφ
200QJ20-65/5 short	7.5	10	18-22	55-75	3*4	3"	18	0.81
200QJ20-65/5 high	7.5	10	18-22	55-75	3*4	2"	18	0.81
200QJ20-81/6 short	10	14	18-22	66-94	3*4	2"	24.7	0.82
200QJ20-81/6 high	10	14	18-22	66-94	3*4	2"	24.7	0.82
200QJ20-93/7	10	14	18-22	79-107	3*4	2"	24.7	0.82
200QJ20-108/8	13	18	18-22	92-125	3*6	2"	29.7	0.83
200QJ20-121/9	13	18	18-22	103-140	3*8	2"	29.7	0.83
200QJ20-135/10	15	20	18-22	115-156	3*6	2"	33.9	0.83
200QJ20-148/11	15	20	18-22	126-170	3*6	2"	33.9	0.83
200QJ20-182/12	18.5	25	18-22	138-187	3*10	2"	41.6	0.83
200QJ20-175/13	18.5	25	18-22	150-210	3*10	2"	41.6	0.83
200QJ20-188/14	22	30	18-22	160-217	3*10	2"	48.2	0.84
200QJ20-202/15	22	30	18-22	172-232	3*10	2"	48.2	0.84
200QJ20-216/16	25	34	18-22	184-249	3*10	2"	54.5	0.84
200QJ20-230/17	25	34	18-22	195-265	3*10	2"	54.5	0.84
200QJ20-243/18	25	34	18-22	206-280	3*10	2"	54.5	0.84
200QJ20-256/19	30	41	18-22	218-295	3*16	2"	65.4	0.84
200QJ20-270/20	30	41	18-22	230-310	3*16	2"	65.4	0.84
200QJ20-283/21	30	41	18-22	240-325	3*16	2"	79.7	0.84
200QJ20-297/22	37	50	18-22	252-341	3*16	2"	79.7	0.84
200QJ20-310/23	37	50	18-22	265-358	3*16	2"	79.7	0.84
200QJ20-324/24	37	50	18-22	275-372	3*16	2"	79.7	0.84
200QJ20-338/25	37	50	18-22	287-388	3*16	2"	79.7	0.84
200QJ20-351/28	45	61	18-22	298-403	3*25	2"	96.9	0.84
200QJ20-365/27	45	61	18-22	310-420	3*25	2"	96.9	0.84
200QJ20-378/28	45	61	18-22	320-435	3*25	2"	96.9	0.84
200QJ20-391/29	45	61	18-22	330-450	3*25	2"	96.9	0.84
200QJ20-405/30	45	61	18-22	345-465	3*25	2"	96.9	0.84
200QJ25-42/3	5.5	7	23-27	40-44	3*2.5	2"	13.6	0.80
200QJ25-56/4	7.5	10	23-27	45-67	3*4	2"	18	0.81
200QJ25-70/5	9.2	13	23-27	56-84	3*4	2"	21.7	0.82
200QJ25-84/6	11	15	23-27	67-100	3*4	2"	25.8	0.82
200QJ25-98/7	11	15	23-27	84-112	3*4	2"	25.8	0.82
200QJ25-112/8	13	18	23-27	96-129	3*6	2"	29.7	0.83

备注：接受客户特殊定制。

Note: Customized is acceptable.

基本参数表 Basic Parameter Table

型号 Model	电机功率 Motor Power		流量范围 Flow Range	扬程范围 Head Range	电缆 Cable	出口尺寸 Outlet Size	额定电流 Rated Current	功率因数 Power Factor
	kW	hp	m ³ /h	m	mm ²	Inch (")	A	cosφ
200QJ25-126/9	15	20	23-27	100-145	3*6	2"	33.9	0.83
200QJ25-140/10	18.5	25	23-27	110-161	3*10	2"	41.6	0.83
200QJ25-154/11	18.5	25	23-27	138-184	3*10	2"	41.6	0.83
200QJ25-168/12	22	30	23-27	140-195	3*10	2"	48.2	0.84
200QJ25-182/13	22	30	23-27	150-210	3*10	2"	48.2	0.84
200QJ25-196/14	25	34	23-27	160-225	3*10	2"	54.5	0.84
200QJ25-210/15	25	34	23-27	180-240	3*10	2"	54.5	0.84
200QJ25-224/16	30	41	23-27	190-258	3*16	2"	65.4	0.84
200QJ25-238/17	30	41	23-27	200-275	3*16	2"	65.4	0.84
200QJ25-252/18	30	41	23-27	210-290	3*16	2"	65.4	0.84
200QJ25-266/19	37	50	23-27	220-305	3*16	2"	79.7	0.84
200QJ25-280/20	37	50	23-27	230-322	3*16	2"	79.7	0.84
200QJ25-294/21	37	50	23-27	250-340	3*16	2"	79.7	0.84
200QJ25-308/22	37	50	23-27	260-355	3*16	2"	79.7	0.84
200QJ32-16/1	3	4	29-35	12-19	3*1.5	3"	7.9	0.78
200QJ32-26/2	4	5	29-35	21-31	3*1.5	3"	10.1	0.79
200QJ32-32/2	5.5	7	29-35	25-38	3*2.5	3"	10.1	0.79
200QJ32-39/3	5.5	7	29-35	32-47	3*2.5	3"	13.6	0.80
200QJ32-48/3	7.5	10	29-35	38-58	3*4	3"	13.6	0.80
200QJ32-52/4	7.5	10	29-35	42-62	3*4	3"	18	0.81
200QJ32-64/4	10	14	29-35	54-77	3*4	3"	24.7	0.82
200QJ32-65/5	10	14	29-35	52-78	3*4	3"	24.7	0.82
200QJ32-78/6	13	18	29-35	53-94	3*6	3"	29.7	0.83
200QJ32-80/5	13	18	29-35	66-96	3*6	3"	29.7	0.83
200QJ32-91/7	15	20	29-35	73-108	3*6	3"	33.9	0.83
200QJ32-96/6	15	20	29-35	77-115	3*6	3"	33.9	0.83
200QJ32-104/8	18.5	25	29-35	84-125	3*10	3"	41.6	0.83
200QJ32-112/7	18.5	25	29-35	80-132	3*10	3"	41.6	0.83
200QJ32-117/9	18.5	25	29-35	94-140	3*10	3"	48.2	0.83
200QJ32-128/8	22	30	29-35	106-150	3*10	3"	48.2	0.84
200QJ32-130/10	22	30	29-35	108-155	3*10	3"	48.2	0.84
200QJ32-143/11	22	30	29-35	121-170	3*10	3"	48.2	0.84
200QJ32-144/9	22	30	29-35	123-172	3*10	3"	54.5	0.84

备注：接受客户特殊定制。

Note: Customized is acceptable.

基本参数表 Basic Parameter Table

型号 Model	电机功率 Motor Power		流量范围 Flow Range	扬程范围 Head Range	电缆 Cable	出口尺寸 Outlet Size	额定电流 Rated Current	功率因数 Power Factor
	kW	hp	m ³ /h	m	mm ²	Inch (")	A	cosφ
QJ Series								
200QJ63-98/7	30	41	58-68	84-114	3*16	3"	65.4	0.84
200QJ63-112/8	30	41	58-68	93-131	3*16	3"	65.4	0.84
200QJ63-126/9	37	50	58-68	100-147	3*16	3"	79.7	0.84
200QJ63-140/10	45	61	58-68	120-164	3*25	3"	96.9	0.84
200QJ63-154/11	45	61	58-68	130-180	3*25	3"	96.9	0.84
200QJ80-11/1	4	5	74-86	8-14	3*1.5	4"	10.1	0.79
200QJ80-22/2	7.5	10	74-86	19-25	3*4	4"	18	0.81
200QJ80-33/3	13	18	74-86	28-37	3*6	4"	29.7	0.83
200QJ80-44/4	15	20	74-86	37-50	3*6	4"	33.9	0.83
200QJ80-55/5	18.5	25	74-86	47-63	3*10	4"	41.6	0.83
200QJ80-66/6	22	30	74-86	56-75	3*10	4"	48.2	0.83
200QJ80-77/7	30	41	74-86	66-88	3*16	4"	65.4	0.84
200QJ80-88/8	30	41	74-86	75-101	3*16	4"	65.4	0.84
200QJ80-99/9	37	50	74-86	84-113	3*16	4"	79.7	0.84
200QJ80-110/10	45	61	74-86	95-125	3*25	4"	96.9	0.84
200QJ80-121/11	45	61	74-86	104-138	3*25	4"	96.9	0.84
200QJ100-15/1	7.5	10	80-120	12-16	3*4	4"	18	0.81
200QJ100-30/2	15	20	80-120	26-32	3*6	4"	33.9	0.82
200QJ100-45/3	22	30	80-120	42-47	3*10	4"	48.2	0.84
200QJ100-60/4	30	41	80-120	58-62	3*16	4"	65.4	0.84
200QJ100-75/5	37	50	80-120	72-77	3*16	4"	79.7	0.84
200QJ100-90/6	45	61	80-120	88-92	3*25	4"	96.9	0.84
200QJ100-105/7	45	61	80-120	102-107	3*25	4"	96.9	0.84
250QJ50-20/1	5.5	7	46-54	17-23	3*2.5	3"	13.6	0.85
250QJ50-33/2	7.5	10	46-54	28-38	3*4	3"	18	0.86
250QJ50-40/2	9.2	13	46-54	34-46	3*4	3"	21.7	0.87
250QJ50-60/3	15	20	46-54	51-68	3*6	3"	33.9	0.83
250QJ50-80/4	18.5	25	46-54	68-92	3*10	3"	40.8	0.84
250QJ50-100/5	25	34	46-54	85-115	3*10	3"	53.8	0.84
250QJ50-120/6	30	41	46-54	102-138	3*16	3"	64.2	0.84
250QJ50-140/7	30	41	46-54	119-161	3*16	3"	64.2	0.84
250QJ50-160/8	37	50	46-54	136-184	3*16	3"	77.8	0.85
250QJ50-180/9	45	61	46-54	150-210	3*25	3"	77.8	0.85
250QJ50-200/10	45	61	46-54	170-230	3*25	3"	94.1	0.85

备注：接受客户特殊定制。

Note: Customized is acceptable.

基本参数表 Basic Parameter Table

型号 Model	电机功率 Motor Power		流量范围 Flow Range	扬程范围 Head Range	电缆 Cable	出口尺寸 Outlet Size	额定电流 Rated Current	功率因数 Power Factor
	kW	hp	m ³ /h	m	mm ²	Inch (")	A	cosφ
QJ Series								
250QJ50-220/11	55	75	46-54	167-253m	3*25	3"	114.3	0.85
250QJ50-240/12	55	75	46-54	204-276	3*25	3"	114.3	0.85
250QJ50-260/13	63	86	46-54	230-290	3*25	3"	127.9	0.85
250QJ50-280/14	63	86	46-54	268-322	3*35	3"	127.9	0.85
250QJ50-300/15	63	86	46-54	265-335	3*35	3"	127.9	0.85
250QJ50-320/16	75	102	46-54	272-368	3*35	3"	152.3	0.86
250QJ50-340/17	75	102	46-54	315-375	3*35	3"	152.3	0.86
250QJ50-360/18	90	122	46-54	330-390	3*50	3"	182.8	0.87
250QJ50-380/19	90	122	46-54	350-410	3*50	3"	182.8	0.87
250QJ50-400/20	100	136	46-54	365-430	3*50	3"	203.1	0.87
250QJ63-20/1	5.5	7	58-68	17-23	3*2.5	3"	13.6	0.80
250QJ63-40/2	11	15	58-68	34-48	3*4	3"	25.8	0.82
250QJ63-60/3	18.5	25	58-68	51-69	3*10	3"	40.8	0.84
250QJ63-80/4	22	30	58-68	68-92	3*10	3"	47.9	0.84
250QJ63-100/5	30	41	58-68	75-100	3*16	3"	64.2	0.84
250QJ63-120/6	37	50	58-68	100-138	3*16	3"	77.8	0.85
250QJ63-160/8	45	61	58-68	130-184	3*25	3"	94.1	0.85
250QJ63-200/10	55	75	58-68	170-230	3*25	3"	114.3	0.85
250QJ63-220/11	63	86	58-68	180-253	3*25	3"	127.9	0.85
250QJ63-260/13	75	102	58-68	220-299	3*35	3"	152.3	0.86
250QJ63-300/15	90	122	58-68	205-343	3*50	3"	182.8	0.86
250QJ80-20/1	7.5	10	74-86	17-23	3*4	4"	18	0.85
250QJ80-40/2	15	20	74-86	34-46	3*6	4"	33.9	0.83
250QJ80-60/3	22	30	74-86	51-69	3*10	4"	47.9	0.84
250QJ80-70/4	25	34	74-86	65-75	3*10	4"	64.2	0.84
250QJ80-80/4	30	41	74-86	68-92	3*16	4"	77.8	0.84
250QJ80-100/5	37	50	74-86	85-115	3*16	4"	77.8	0.85
250QJ80-120/6	45	61	74-86	102-138	3*25	4"	94.1	0.85
250QJ80-140/7	55	75	74-86	118-163	3*25	4"	114.3	0.85
250QJ80-160/8	55	75	74-86	136-184	3*25	4"	114.3	0.85
250QJ80-180/9	63	86	74-86	153-207	3*35	4"	127.9	0.86
250QJ80-200/10	75	102	74-86	170-230	3*35	4"	152.3	0.86
250QJ80-220/11	90	122	74-86	190-250	3*35	4"	152.3	0.86
250QJ80-240/12	90	122	74-86	204-276	3*50	4"	182.3	0.86

备注：接受客户特殊定制。

Note: Customized is acceptable.

基本参数表 Basic Parameter Table

型号 Model	电机功率 Motor Power		流量范围 Flow Range	扬程范围 Head Range	电缆 Cable	出口尺寸 Outlet Size	额定电流 Rated Current	功率因数 Power Factor
	kW	hp						
QJ Series	kW	hp	m ³ /h	m	mm ²	Inch (")	A	cosφ
250QJ80-260/13	100	136	74-86	220-280	3*50	4"	203.1	0.86
250QJ80-280/14	110	150	74-86	235-325	3*50	4"	223.4	0.86
250QJ100-18/1	7.5	10	80-120	16-21	3*4	4"	18	0.86
250QJ100-36/2	15	20	80-120	32-42	3*6	4"	33.9	0.83
250QJ100-54/3	25	34	80-120	48-63	3*10	4"	53.8	0.84
250QJ100-72/4	30	41	80-120	64-84	3*16	4"	64.2	0.84
250QJ100-80/5	45	61	80-120	68-92	3*25	4"	94.1	0.85
250QJ100-108/6	45	61	80-120	96-128	3*25	4"	94.1	0.85
250QJ100-126/7	55	75	80-120	110-147	3*25	4"	114.3	0.85
250QJ100-144/8	63	86	80-120	120-168	3*35	4"	127.9	0.85
250QJ100-162/9	75	102	80-120	140-189	3*35	4"	152.3	0.86
250QJ100-198/11	90	122	80-120	170-231	3*50	4"	182.8	0.86
250QJ100-216/12	100	136	80-120	190-252	3*50	4"	203.1	0.86
250QJ125-16/1	9.2	13	116-134	13-19	3*4	5"	21.7	0.87
250QJ125-32/2	18.5	25	116-134	27-37	3*10	5"	40.8	0.84
250QJ125-48/3	25	34	116-134	40-56	3*10	5"	53.8	0.84
250QJ125-84/4	37	50	116-134	54-73	3*16	5"	77.8	0.85
250QJ125-80/5	45	61	116-134	68-92	3*25	5"	94.1	0.85
250QJ125-96/6	55	75	116-134	82-110	3*25	5"	114.3	0.85
250QJ125-112/7	63	86	116-134	95-128	3*35	5"	127.9	0.85
250QJ125-128/8	75	102	116-134	109-147	3*35	5"	152.3	0.86
250QJ125-144/9	90	122	116-134	124-164	3*50	5"	182.8	0.86
250QJ125-160/10	90	122	116-134	136-184	3*50	5"	182.8	0.86
250QJ125-176/11	100	136	116-134	150-202	3*50	5"	203.1	0.86
250QJ125-192/12	110	150	116-134	163-220	3*50	5"	223.4	0.86
250QJ140-15/1	9.2	13	130-150	13-17	3*4	5"	21.7	0.87
250QJ140-22/1	13	18	130-145	17-26	3*6	5"	30.1	0.82
250QJ140-30/2	18.5	25	130-150	26-34	3*10	5"	40.8	0.84
250QJ140-45/3	30	41	130-145	40-52	3*16	5"	64.2	0.84
250QJ140-60/4	37	50	130-150	52-68	3*16	5"	77.8	0.85
250QJ140-75/5	45	61	130-145	65-86	3*25	5"	94.1	0.85
250QJ140-90/6	55	75	130-150	78-103	3*25	5"	114.3	0.85
250QJ140-105/7	63	86	130-145	91-120	3*35	5"	127.9	0.85
250QJ140-120/8	75	102	130-150	104-137	3*35	5"	152.3	0.86

备注：接受客户特殊定制。

Note: Customized is acceptable.

基本参数表 Basic Parameter Table

型号 Model	电机功率 Motor Power		流量范围 Flow Range	扬程范围 Head Range	电缆 Cable	出口尺寸 Outlet Size	额定电流 Rated Current	功率因数 Power Factor
	kW	hp						
QJ Series	kW	hp	m ³ /h	m	mm ²	Inch (")	A	cosφ
250QJ140-135/9	90	122	130-145	114-156	3*50	5"	182.8	0.86
250QJ140-150/10	100	136	130-150	130-171	3*50	5"	203.1	0.86
250QJ140-165/11	110	150	143-188	158-162	3*50	5"	223.4	0.86
250QJ140-180/12	125	170	130-145	158-205	3*50	5"	242	0.87
250QJ160-15/1	13	18	148-172	40-50	3*6	5"	30.1	0.82
250QJ160-30/2	22	30	148-172	25-35	3*10	5"	47.9	0.84
250QJ160-45/3	30	41	148-172	38-51	3*16	5"	64.2	0.85
250QJ160-60/4	45	61	148-172	52-69	3*16	5"	94.1	0.85
250QJ160-75/5	55	75	148-172	65-86	3*25	5"	114.3	0.85
250QJ160-90/6	63	86	148-172	77-103	3*35	5"	127.9	0.86
250QJ160-105/7	75	102	148-172	90-120	3*35	5"	152.3	0.86
250QJ160-120/8	90	122	148-172	102-138	3*50	5"	182.8	0.86
250QJ160-135/9	100	136	148-172	115-155	3*50	5"	203.1	0.86
250QJ160-150/10	110	150	186-214	128-170	3*50	5"	222.1	0.87
300QJ200-20/1	18.5	25	186-214	17-23	3*10	6"	41.7	0.84
300QJ200-30/1	25	34	186-214	27-33	3*10	6"	53.8	0.85
300QJ200-40/2	37	50	186-214	35-45	3*16	6"	77.8	0.85
300QJ200-60/3	55	75	186-214	51-69	3*25	6"	115	0.86
300QJ200-80/4	75	102	186-214	68-92	3*35	6"	154.1	0.86
300QJ200-100/5	90	122	186-214	85-115	3*50	6"	183.8	0.87
300QJ200-120/6	110	150	186-214	100-138	3*50	6"	222.1	0.87
300QJ240-22/1	22	30	223-257	18-25	3*10	6"	47.9	0.84
300QJ240-44/2	45	61	223-257	37-51	3*25	6"	94.1	0.85
300QJ240-66/3	75	102	223-257	56-76	3*35	6"	152.3	0.86
300QJ240-88/4	100	136	223-257	75-101	3*50	6"	203.1	0.86
300QJ240-110/5	100	136	223-257	95-125	3*50	6"	203.1	0.87
300QJ300-20/1	25	34	279-321	17-23	3*10	6"	53.8	0.84
300QJ300-40/2	55	75	279-321	35-45	3*25	6"	115	0.85
300QJ300-60/3	75	102	279-321	51-69	3*35	6"	154.1	0.86
300QJ300-80/4	110	150	279-321	68-92	3*50	6"	223.4	0.87
300QJ400-40/1	75	102	368-432	38-42	3*35	8"	152.3	0.86
300QJ400-80/2	180	248	368-432	78-84	3*70	8"	284.4	0.85
300QJ400-120/3	220	299	368-432	117-123	3*95	8"	439.2	0.86

备注：接受客户特殊定制。

Note: Customized is acceptable.

基本参数表 Basic Parameter Table

型号 Model	电机功率 Motor Power		流量范围 Flow Range	扬程范围 Head Range	电缆 Cable	出口尺寸 Outlet Size	额定电流 Rated Current	功率因数 Power Factor
	kW	hp						
QJ Series			m ³ /h	m	mm ²	Inch (")	A	cosφ
300QJ500-15/1	30	41	460-540	14-16	3*16	8"	64.2	0.84
300QJ500-30/2	75	102	460-540	29-32	3*35	8"	131.7	0.85
300QJ500-45/3	110	150	460-540	43-47	3*50	8"	222.1	0.86
300QJ500-60/4	140	190	460-540	57-63	3*70	8"	249.5	0.87
300QJ500-75/5	185	252	460-540	72-78	3*95	8"	317.5	0.87
300QJ500-90/6	220	299	460-540	87-93	3*95	8"	439.2	0.87
350QJ250-25/1	30	41	233-267	22-28	3*16	6"	64.2	0.85
350QJ250-50/2	63	86	233-267	47-53	3*35	6"	127.9	0.86
350QJ250-75/3	90	122	233-267	72-78	3*50	6"	183.8	0.87
350QJ250-100/4	125	170	233-267	95-105	3*70	6"	242	0.87
350QJ250-125/5	160	218	233-267	120-130	3*95	6"	284.4	0.85
350QJ320-20/1	30	41	305-335	18-22	3*16	8"	64.2	0.85
350QJ320-30/1	45	61	305-335	28-32	3*25	8"	94.1	0.86
350QJ320-40/2	63	86	305-335	38-42	3*35	8"	127.9	0.86
350QJ320-60/2	90	122	305-335	57-63	3*50	8"	183.8	0.87
350QJ320-90/3	140	190	305-335	85-95	3*70	8"	249.5	0.87
350QJ320-120/4	185	252	305-335	115-125	3*95	8"	367.1	0.87
400QJ400-50/1	90	122	388-416	48-52	3*50	8"	183.8	0.87
400QJ500-20/1	45	61	460-540	18-22	3*25	8"	94.1	0.86
400QJ500-40/1	90	122	460-540	38-42	3*50	8"	183.8	0.87
400QJ500-80/2	185	252	460-540	77-83	3*95	8"	367.1	0.87
450QJ800-16/1	75	102	750-850	12-20	3*35	12"	131.7	0.86
450QJ1000-16/1	90	122	900-1200	12-20	3*50	12"	183.8	0.87
500QJ640-26/1	90	122	600-680	26-30	3*50	10"	183.8	0.87
500QJ640-56/2	185	252	600-680	54-58	3*95	10"	367.1	0.87
500QJ640-84/3	260	354	600-680	82-86	3*150	10"	558.2	0.87
550QJ1200-18/1	110	150	1100-1400	15-22	3*50	16"	222.1	0.87
600QJ800-25/1	110	150	750-850	23-27	3*50	12"	222.1	0.87
600QJ800-50/2	220	299	750-850	48-52	3*95	12"	439.2	0.87
600QJ800-75/3	300	408	750-850	73-77	3*185	12"	622.1	0.87
600QJ1000-20/1	110	150	900-1200	18-22	3*50	12"	222.1	0.87
600QJ1000-40/2	220	299	900-1200	38-42	3*95	12"	439.2	0.87
600QJ1000-60/3	300	408	900-1200	58-62	3*185	12"	622.1	0.87

备注：接受客户特殊定制。

Note: Customized is acceptable.

使用条件 Use Conditions

使用条件：

1. 电压偏差不得超过±5%，频率偏差不得超过±1%的三相电源；
2. 电机腔内腔必须注满清水；
3. 水泵的第一级叶轮至少应浸入动水位以下2米，水泵机组浸入静水位以下不得大于70米，电机底部距离井底不得小于3米；
4. 水源出水量应保证水泵连续运转的需求；
5. 如果用于水池使用，必须给电机加装导流罩降温。

Use Conditions:

1. The three-phase power supply voltage deviation does not exceed ±5% and the frequency deviation is not more than ±1%;
2. Motor cavity must be filled full with clean water during operation;
3. The first stage impeller of the pump shall be immersed at least 2 meters below the dynamic water level. The pump unit shall not be more than 70 meters below the static water level. The bottom of the motor shall not be less than 3 meters from the bottom of the well;
4. Ensure the source of water is enough for pump operating continuously;
5. If it is used in pool, should add guide tube for pump motor in order to cooling.

安装工具:

1. 吊链一副；
2. 垂直高度不低于4米的三角架一个；
3. 能承受一吨重的吊绳（钢丝绳）两根；
4. 安装卡箍、夹板两副；
5. 扳手、手锤、螺丝刀、电工工具及仪表等。

Installation tools:

1. Set of sling chains;
2. Tripod with a vertical of height over 4m;
3. Two pendant cord (steel wire rope) bearing weight in excess of 1 ton;
4. Two sets of clamps and splints;
5. Spanner, hammer, screwdriver, electrician tools and instrument.

拆卸放气孔丝堵
Disassemble the gas vent plug;



使用前给电机注水
Fill water before operating;



备注：接受客户特殊定制。

Note: Customized is acceptable.